



HDR-15W单组输出导轨电源

HDR-15W Single output DIN rail power supply

概述 Summary

- > 单组输出: 功率15W
Single output: power 15W
- > 输入电压: 85 ~ 264VAC/120 ~ 370VDC
Input voltage: 85 ~ 264VAC/120 ~ 370VDC



常见规格 General Specification

17.5 × 90 × 54.5mm

性能 Specification	型号 Model	HDR-15-5	HDR-15-12	HDR-15-24	HDR-15-48
直流输出电压、电流 DC output voltage, current		5V 0~2.4A	12V 0~1.25A	24V 0~0.63A	48V 0~0.32A
纹波及噪音 Wave and noise		80mVp-p	120mVp-p	150mVp-p	240mVp-p
进线稳定度 Inlet wire stability		± 1%	± 1%	± 1%	± 1%
负载稳定度 Load stability		± 1%	± 1%	± 1%	± 1%
效率 Efficiency		78%	83%	84%	85%
直流电压可调范围 Adjustable range for DC voltage		± 10%	± 10%	± 10%	± 10%
输入电压范围 Input voltage range		85 ~ 264V交流/120 370V直流 47 ~ 63Hz 85 ~ 264VAC/120 ~ 370VDC 47 ~ 63Hz			
冲击电流 Impact current		冷启动电流 25A/115VAC 45A/230VAC Cold start current			
过载保护 Overload protection		110% ~ 150%切断输出, 自动恢复 110% ~ 150% cut off the output, automatic recovery			
过电压保护 Overvoltage protection		115% ~ 140%额定输出功率 保护类型: 打嗝模式, 故障排除后自动回复 115% ~ 140% rated output power Protection type: Hiccups mode, recovers automatically after fault condition is removed			
启动、上升、保持时间 Setup, rise, hold up time		2000ms, 80ms/230VAC 2000ms, 80ms/115VAC(满载时)			
耐压性 Withstand voltage		输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100M I/P-O/P I/P-FG O/P-FG: 100M Ohms / 500VDC / 25°C / 70%RH			
工作温度 Working temperature		-20°C ~ +70°C			
尺寸 Dimension		17.5 × 90 × 54.5mm			
重量 Weight		0.08kg			
包装 Packing		42.5 × 34 × 19.5CM/140PCS/12kg			

外形尺寸 Overall dimension(mm)

接线位置


- 端口3,4: 交流输入
- 端口1: 直流输出+V
- 端口2: 直流输出-V

Terminal Pin No. Assignment

- Pin 3,4: AC input
- Pin 1: DC output +V
- Pin 2: DC output -V

端子Pin脚定义

Pin脚编号	Pin脚功能	Pin脚编号	Pin脚功能
1	+V	3	AC/N
2	-V	4	AC/L



ADM ES BLE DN-RAIL:TS35/7.5 OR TS35/15

